

SPECIFICATION FOR APPROVAL

DOCUMENT DATE: 2025/5/6

电话：13682686800

规格书/SPECIFICATIONS

揭阳市领界电子有限公司/JIEYANGSHI LINGJIE DIANZIYOUXIANGONGSI

描述/DESCRIPTION	型号	客户料号/USER PART NO.
电感 TRANSFORMER	EE8.3-1MH	

2022/7/25		新规格发行 New specification issued	A/0	李国栋	蔡冰
-----------	--	-----------------------------------	-----	-----	----


1. 外形尺寸图/PHYSICAL DIMENSION: (单位/UNIT: mm)

制图/DRAFTED BY	审核/CHECKED BY	批准/APPROVED BY	页面/PAGE OF 5
杨晓梅	黄春葵	蔡冰	日期/DATE 2025/5/6


规格书/SPECIFICATIONS

揭阳市领界电子有限公司/JIEYANGSHI LINGJIE DIANZIYOUXIANGONSI


描述/DESCRIPTION	型号	客户料号/USER PART NO.
电感 TRANSFOMER	EE8.3-1MH	




FRONT VIEW (正视图)



SIDE VIEW (侧视图)



BOTTOM VIEW (底视图)



TOP VIEW (顶视图)

型号: EE8.3

DIM	A	B	C	D	E	F	G
mm	9.50	9.50	9.50	3.5	5.0	6.8	0.5*0.5
SPEC	MAX	MAX	MAX	±0.5	±0.5	±0.5	±0.1

备注:

- 1.骨架为 EE8.3 卧式 全脚.
- 2.磁芯用浅黄色胶带包固定.
- 3.产品需含浸.


2. 电气连接图/SCHEMATIC DIAGRAM:

制图/DRAFTED BY	审核/CHECKED BY	批准/APPROVED BY	页面/PAGE OF 5
杨晓梅	黄春葵	蔡冰	日期/DATE 2025/5/6


规格书/SPECIFICATIONS

揭阳市领界电子有限公司/JIEYANGSHI LINGJIE DIANZIYOUXIANGONGSI

描述/DESCRIPTION	型号	客户料号/USER PART NO.
电感 TRANSFOMER	EE8.3-1MH	



3. 绕组结构图/WINDING LIST



绕组 NO.	脚位 TERMINAL	线径 WIRE	圈数 (仅供参考, 感量为准) TURNS	绝缘胶带 INSULATTON TAPE
N1	1-2	0.2mm 2UEW	25T REF	2TS
N2	4-3	0.2mm 2UEW	25T REF	

制图/DRAFTED BY	审核/CHECKED BY	批准/APPROVED BY	页面/PAGE OF 5
杨晓梅	黄春葵	蔡冰	日期/DATE 2025/5/6

规格书/SPECIFICATIONs

揭阳市领界电子有限公司/JIEYANGSHI LINGJIE DIANZIYOUXIANGONSI

描述/DESCRIPTION	型号	客户料号/USER PART NO.
电感 TRANSFOMER	EE8.3-1MH	

4. 电气特性/ELECTRICAL CHARACTERISTICS:

温度 25℃ 湿度 65%±20% RH (TEMPERATURE AT 25℃ HUMIDTY AT 65±20% RH)

TEST PROJEET 测试项目	TEST PIN 测试脚位	SPECIFICATION 测试规格	TEST CONDITION 测试条件	TESTER 测试机
电感	L1-2 L3-4	1MH min	1KHZ 0.25V	TH2817CX
高压	COIL-COIL COIL-CORE	1000V AC	50HZ 5mA 3S	19053
		800V AC	50HZ 5mA 3S	
绝缘电阻 (MΩ)	COIL-CORE	100MΩ MIN	@ DC 500V	

5. 材料清单/MATERIAL LIST

No.	PART	MATERIAL	MANUFACTURER	RATING	SIZE	UL FILE NO.
1	CORE 磁芯	AL=3500 MIN	SHANGDONG HENGRUI MAGNET TECHNOLOGY CO., LTD.LTD OR EOUIVALENT	N/A	EE8.3	N/A
2	BOBBIN 骨架	T375HF	CHANG CHUN PLASTIC CO., LTD	150℃	EE8.3	E59481
3	WIRE 铜线	xUEW/155, QA-x/155	NINBO JINTIAN NEW MATERIALCO., LTD OR EOUIVALENT	155℃	0.23mm	E348247
4	VARNISH 凡立水	HMT	ZHUHAI CHANGXIAN NEWMATERIALS TECHNOLOGY CO.,LTD OR EOUIVALENT	130℃	N/A	E335405
5	TAPE	E962	SHENZHEN XINHUAHUI ELECTRONIC MATERIALS CO.,LTD OR EOUIVALENT	130℃	0.025mm/t	E328315

制图/DRAFTED BY	审核/CHECKED BY	批准/APPROVED BY	页面/PAGE OF 5
杨晓梅	黄春葵	蔡冰	日期/DATE 2025/5/6

规格书/SPECIFICATIONS

揭阳市领界电子有限公司/JIEYANGSHI LINGJIE DIANZIYOUXIANGONSI

描述/DESCRIPTION	型号	客户料号/USER PART NO.
电感 TRANSFOMER	EE8.3-1MH	

QUANTITY 数量		5PCS	DESCRIPTION 描述			EE8. 3		TEST CONDITION:1EHZ/0. 25V INDUCTANCE: @ KHZ/				
TEMPERATURE 温度		25℃	HUMIDITY 湿度			60%						
TEST INSTRUMENT		☐ CH-310 ☐ CH-301 ☒ CH-502 ☐ CH-100 ☒ CH-4284A										
		☒ TH2817CX ☐ CH-1302 ☒ 19053 ☒ CH-1062 ☐ CH-3205B										
HI-POT AC 50HZ 5MA 3SEC	COIL-COIL	1000V	OK	OK	OK	OK	OK					
	COIL-CORE	800V	OK	OK	OK	OK	OK					
DIMENSION 尺寸	A	9.50MAX	9.24	9.30	9.25	9.27	9.26					
	B	9.50MAX	9.16	9.06	9.13	9.15	9.11					
	C	9.50MAX	9.10	9.08	9.12	9.10	9.11					
	D	3.5±0.5	3.23	3.30	3.27	3.25	3.28					
	E	5.0±0.5	4.98	4.93	4.95	4.96	4.99					
	F	6.8±0.5	6.79	6.80	6.79	6.75	6.76					
	G	0.5*0.5±0.1	0.52	0.51	0.53	0.53	0.52					
TRUNS			OK	OK	OK	OK	OK					

制图/DRAFTED BY	审核/CHECKED BY	批准/APPROVED BY	页面/PAGE OF 5
杨晓梅	黄春葵	蔡冰	日期/DATE 2025/5/6